

GG-CL₂-B

CHLORINE SENSOR



Key Features

- Chlorine specific electrochemical sensor technology
- Electronics completely potted to prevent corrosion in harsh environments
- Industry standard linear 4-20 mA output
- Corrosion, weather, and chemical resistant polycarbonate sensor enclosure
- Intelligent-design enclosure temperature control for improved cell life
- Sensor designed to adapt to any harsh environment from -50°F to +122°F
- Real-time continuous monitoring for early detection of toxic concentrations
- Accurately monitor OSHA's PEL, STEL, and IDLH setpoints
- Detection range of 0-5 ppm Cl₂

Toxic chlorine gas detection designed 'food industry' tough.

The GG-CL2-B utilizes proven electrochemical sensor technology for fast and accurate detection. The standard detection range of the GG-CL2-B provides real-time continuous monitoring of chlorine concentrations accurately down to 0.5 ppm, with no false alarms.

The intelligent internal temperature control of the GG-CL2-B provides optimum temperature control for extended cell life. The high-quality injection-molded polycarbonate enclosure offers excellent chemical corrosion protection and high impact resistance.

The GG-CL2-B provides an industry standard linear 4-20 mA output signal compatible with most gas detection systems and PLCs. The output signal is not affected by drastic temperature variations or other atmospheric conditions.

Applications

• Process Areas	• Indoor Pools
• Tank Storage	• Sanitizing Systems
• Injection Systems	• Air Monitoring

Benefits

- Low cost
- Simple operation
- Rugged and reliable

The standard **GG-CL2-B** sensor is designed to work anywhere, and at a lower base-model price than most competing models. With only one electrochemical sensor for any application; designing, ordering, and maintaining your chlorine detection system is simple.

Designed "Food Industry" tough

The **GG-CL2-B** is prepared to survive in just about any harsh industrial condition, including acid washdown of processing areas. Every circuit board is sealed forever in potting compound, protecting electronic components and copper tracing from corrosion. A specially vented chemical-resistant polycarbonate enclosure protects the sensor from accidental damage, weather, and direct hose-hits from clean-up crews.


Ordering Information

The **GG-CL2-B** is delivered calibrated and ready to install. Use the model numbers below to order.

Order #: [GG-CL2-B-5](#) (standard)
[GG-CL2-B-5-ST](#) (stainless enclosure)
[GG-CL2-B-RC](#) (replacement cell)
[GG-CL2-B-5-DM](#) (duct mount)



Stainless steel enclosure option



SPECIFICATIONS

Due to ongoing research and product improvement, specifications are subject to change

Input Power:
+24 VDC, 350 mA

Detection Principle:
Electrochemical

Detection Method:
Diffusion

Gases:
Chlorine (CL2)

Ranges:
0-5 ppm

Output Signal:
Linear 4-20 mA (max input impedance: 700 Ohms)

Linearity:
+/- 0.5% of full-scale

Repeatability:
+/- 1% of full-scale

Response Time:
T50 = less than 60 seconds
T90 = less than 90 seconds

Accuracy:
+/- 5% of value, but dependent on calibration gas accuracy and time since last calibration

Zero Drift:
Less than 0.1% of full-scale per month, non-cumulative

Span Drift:
Application dependent, but generally less than 3% per month

Temperature Range:
-50°F to +122°F (-45.6°C to +50°C)

Humidity Range:
5% to 100% condensing

Wiring Connections:
3 conductor, shielded, stranded, 20 AWG cable (General Cable C2525A or equivalent) up to 1500 ft

Terminal Block Plugs (Field Wiring)
12-26 AWG, torque 4 lbs-in

Enclosure:
NEMA 3RX injection-molded, washdown-duty polycarbonate sensor housing with hinged lid and captive screw. For non-classified areas. Optional 316 18 GA, NEMA 3RX washdown-duty stainless steel housing with hinged lid and captive screw. For non-classified areas

Dimensions:
7.5" high x 6.5" wide x 3.75" deep

Weight:
2.15 lbs

Certification:
SGS listed to UL 61010-1, and CSA C22.2 No. 61010-1-12

Warranty:
2-years (including replacement cell)

